

起重量Lifting Weight				t	5						10										
跨度span				m	10.5	13.5	16.5	19.5	22.5	25.5	28.5	31.5	10.5	13.5	16.5	19.5	22.5	25.5	28.5		
起升高度 Lifting height		主钩 main hook		m	16						16										
		副钩 auxiliary hook																			
起升 Hoisting	主 main	A5		m/ min	11.3						8.5										
		A6			15.6						10.4										
	副 auxiliary																				
小车运行 Travelling of crab		37.2						43.8													
大车运行 Travelling of trolley		A5			89.8				91.8		89.8			91.9		84.7					
		A6			92.7				93.7		92.7			93.7		86.5					
起升 Hoisting	主 main	A5		型号 Type / kw	YZR180L-8 / 13kw						YZR180L-6 / 17kw										
		A6			YZR180L-6 / 15kw						YZR200L-6 / 22kw										
	付 auxiliary																				
小车运行 Travelling of crab		YZR112M-6 / 1.8kw						YZR132M ₁ -6 / 2.5kw													
大车运行 Travelling of trolley		A5			YZR132M ₂ -6 / 2 × 4kw				YZR160M ₁ -6 / 2 × 6 .3kw		YZR132M ₂ -6 / 2 × 4kw				YZR160M ₂ -6 / 2 × 6.3						
		A6			YZR160M ₁ -6 / 2 × 5.5kw				YZR160M ₂ -6 / 2 × 7.5kw		YZR160M ₁ -6 / 2 × 5.5kw				YZR160M ₂ -6 / 2 × 7.5						
主要尺寸(mm) Main Dimensions				A5	B ₀	5054		5204		5948		5704		5882		5948					
					B	3400		3550		5000		4050				5000					
					S ₂	800						1050									
					S ₃	1250						1300									
					b	230						230									
					K	1400						2000									
					B _x	1100						1400									
					H	1763						1876				1920					
					H ₁	765+H0						765				815+H					
					H ₂	-24	126	226	376	526	676	826	976	-24	126	226	376	526	628	778	
				H ₃	2396	2546	2646	2796	2946	3096	3246	3396	2396	2546	2646	2796	2946	3048	3198		
				A6	H ₄	71						602						552			
					B	5058		5208		6028		5708				5848		6388			
					W	3400		3550		5000		4050				5000					
					S ₂	800						1050									
					S ₃	1250						1300									
					b	230						230									
					K	1400						2000									
					B _x	1100						1400									
					H	1763						1876				1920					
					H ₁	765				800		765				850					
				H ₂	-24	126	226	376	526	676	826	976	-24	126	226	376	526	628	778		
				H ₃	2396	2546	2646	2796	2946	3096	3246	3396	2396	2546	2646	2796	2946	3048	3198		
				H ₄	71						602						552				
小车 crab		A5	Kg	2500						3400											
		A6		2550						3500											
总重 Total weight		A5	Kg	12715	14233	16061	18616	20977	25393	28516	31405	14270	16151	18881	20677	23517	27605	3098			
		A6		12991	14509	16337	19027	21395	25584	28707	31596	14719	16600	19330	21034	23523	27889	3128			
最大轮压 wheel pressure		A5	KN	74	79	85	92	98	110	118	125	102	109	118	123	130	142	151			
		A6		75	80	86	93	100	111	119	126	104	111	120	125	132	144	152			
钢轨Steel track recommended				43Kg / m																	
电源 Power source				三相交流、three-phase A.C 50HZ、380V																	

起重量Lifting Weight			t	32 / 5							50 / 10								
跨度span			m	10.5	13.5	16.5	19.5	22.5	25.5	28.5	31.5	10.5	13.5	16.5	19.5	22.5	25.5	28.5	
起升高度 Lifting height	主钩 main hook		m	16							12								
	副钩 auxiliary hook			18							16								
起升 Hoisting	主 main	A5	m/ min	7.5							5.9								
		A6		9.5							7.8								
副 auxiliary		15.5							10.4										
小车运行 Travelling of crab		42.4							38.5										
大车运行 Travelling of trolley		A5		87.6			74.2		74.6		74.6								
		A6	89			75.3		75.3		75			76.6						
起升 Hoisting	主 main	A5	型号 Type / kw	YZR280S-10 / 42							YZR280M-10 / 55								
		A6		YZR280M-8 / 55							YZR315S-8 / 75								
付 auxiliary		YZR180L-6 / 17							YZR200L-6 / 26										
小车运行 Travelling of crab		YZR160M-6 / 6.3							YZR160M ₂ -6 / 8. 5										
大车运行 Travelling of trolley		A5		YZR160M ₂ -6 / 2 × 8.5				YZR160L-6 / 2 × 13			YZR180L-8 / 2 × 13								
		A6	YZR160L-6 / 2 × 11				YZR180L-8 / 2 × 11			YZR180L-8 / 2 × 11			YZR200L-8 / 2 × 13						
主要尺寸(mm) Main Dimensions			A5	B _Q	6478			6628		6928		6828		6858		7058			
				B	4650			4700		5000		4800			5000				
				S ₁	1070							1005							
				S ₂	2050							2200							
				S ₃	1700							2000							
				S ₄	2680							3195							
				b	260			300			300								
				K	2500							2500							
				B _x	2800							3580							
				H	2337	2339		2469			2746		2752						
				H ₁	905			1035			1055		1090						
				H ₂	90	94	244	264	414	564	714	814	-79	96	102	252	402	552	702
				H ₃	2510	2514	2664	2684	2834	2984	3134	3234	2541	2516	2522	2672	2822	2972	3122
				H ₄	705	701		571			1020		1014						
				H ₅	790							948							
				A6	B _Q	6588			6608		6828		6828		6858		7058		
			B		4650			4700		5000		4800			5000				
			S ₁		1070							1005							
			S ₂		2050							2200							
			S ₃		1700							2000							
			S ₄		2680							3195							
			b		260			300			300								
			K		2500							2500							
			B _x		2800							3580							
			H		2337	2341		2471			2746		2748	2754					
			H ₁		905			1070			1055		1090						
			H ₂		90	94	244	264	414	564	714	814	-79	98	104	254	404	554	704
			H ₃	2510	2514	2664	2684	2834	2984	3134	3234	2341	2518	2524	2674	2824	2974	3124	
H ₄	705	701		571			1020		1018		1012								
H ₅	790							948											
小车crab		A5	Kg	10877							15425								
		A6		11652							16400								
总重Total weight		A5	Kg	26901	28662	32121	36522	39844	44962	49211	52748	35317	37788	42042	46140	50082	55590	59592	
		A6		28061	30292	33412	38607	42832	47023	50586	55272	36075	38929	43314	47720	51746	57614	61723	
最大轮压 wheel pressure		A5	KN	237	250	262	275	289	305	317	327	333	345	373	385	404	421	434	
		A6		242	255	268	285	299	312	322	335	336	357	377	395	410	428	441	
钢轨 Steel track recommended			QU70或方钢90 or square steel 90							QU80或方钢100 or square steel 100									
电源 Power source			三相交流、three-phase A.C.50HZ、380V																